

Product Codes:
AUGC-REMOTE &
AUGC-REMOTE-LP
(optional low-pressure valve)

AUTOSAVE URINAL FLUSH CONTROL – REMOTE

AUTOSAVE UFC-REMOTE

Product Specification

230 VAC mains operated **15 mm timed urinal flushing control with remotely mounted PIR sensor for concealed cisterns** – the complete 'fit & forget' solution for concealed cisterns such as those fitted behind vanity panels and trims.

This is the latest version of our mains-powered controls, with an outstanding record for reliability and long service. **The Autosave-UFC-REMOTE** saves water by flushing urinals only after use. A remote infrared PIR sensor detects individuals in the washroom and initiates a cistern fill and flush cycle at a preset time following detection.

A simple pushbutton setup procedure sets the cistern fill time. A programmable switch enables the installer to choose the flushing frequency and to set a hygiene flush interval for periods when the building is unoccupied.



Product Features

- 6–12-month typical payback period
- Save up to 80% on metered water bills
- Guaranteed for one year
- WRAS approved valve
- Integral solenoid valve control box and a remote PIR sensor box
- Simple one button setup procedure
- Programmable flush delay and 12 or 24-hour hygiene flush
- Magi-test function
- Suitable for left-hand or right-hand water inlet
- Fail-safe valve – closes if power is removed
- No need to reset after power cut
- Locking screws provided to prevent unauthorised opening
- Fitting kit includes isolating valve, cable gland, locking screws, fixing screws and installation instructions



Saving more than water

watersavers.co.uk | T 01603 720999 | E info@watersavers.co.uk

Watersavers Ltd
Church Field Road
Chilton Industrial Estate
Sudbury
Suffolk CO10 2YA

Designed & Manufactured
in the UK



Specifications

Detection	Remotely mounted passive infrared sensor, range approximately 4 m, coverage 100° from perpendicular
Solenoid Valve	Brass normally closed, 15 mm compression fittings, 2.4 mm orifice, pressure range 0–12 bar with mesh filter (optional low-pressure valve for tank fed installations)
Other Valve Specification	Please contact us.
Cistern Fill Time	1 to 34 minutes – set by simple pushbutton routine.
Flush Program Options	Flush delay (time from detection to actual flush) 5–35 minutes in 5-minute increments, hygiene flush 12 or 24-hour.
Test Function	Magi-test device, provides instant full functional test including valve, infrared PIR sensor operation, battery status, water supply and cistern fill time
Power	230 VAC/50 Hz 10 VA maximum, cable entry through IP65 gland on RHS of enclosure
Enclosure	Size 126 x 96 x 41 mm (exc. valve) in white RAL 9010
Approvals	All Autosave products use WRAS approved valves

Optional Extras

Magi-Test Wand

Telescopic test wand for use with the Autosave controls.



Saving more than water

watersavers.co.uk | T 01603 720999 | E info@watersavers.co.uk

Watersavers Ltd
Church Field Road
Chilton Industrial Estate
Sudbury
Suffolk CO10 2YA

Designed & Manufactured
in the UK

